

TR/RP NO. 62

UNITED STATES NAVAL POSTGRADUATE SCHOOL



A METHOD FOR COMPUTING SERIES SYSTEM
RELIABILITY WITH UNEQUAL COMPONENT
SAMPLE SIZES

by

J. R. Borsting

W. M. Woods

January 1966

Technical Report/Research Paper No. 62

DISTRIBUTION OF THIS DOCUMENT IS UNLIMITED

TA7
.U62
no.62

LIBRARY
NAVAL POSTGRADUATE SCHOOL
MONTEREY, CALIF. 93940

TR 7.462 170.62

UNITED STATES NAVAL POSTGRADUATE SCHOOL
Monterey, California

Rear Admiral E. J. O'Donnell, USN

Superintendent

Dr. R. F. Rinehart,

Academic Dean

ABSTRACT:

A method is presented for constructing system reliability using component failure data when the sample sizes for testing on the component parts differ greatly. The procedure can be applied to weapons systems as easily as subsystems. No assumptions about failure distributions are made. The accuracy of the procedure was examined by computer simulations and in this manner the procedure has demonstrated high accuracy for cases of practical interest.

This task was supported by: Special Projects; Code SP-114

Prepared by: J. R. Borsting
W. M. Woods

Approved by:

J. R. Borsting
Chairman, Department of
Operations Analysis

Released by:

C. E. Menneken
Dean of
Research Administration

U. S. Naval Postgraduate School Technical Report/Research Paper No. 62
January 1966

UNCLASSIFIED

A METHOD FOR COMPUTING SERIES SYSTEM RELIABILITY WITH UNEQUAL COMPONENT SAMPLE SIZES

1. Summary

A procedure has been constructed for obtaining a lower confidence interval on system reliability using component failure data when component sample sizes differ greatly. Although the authors feel the accuracy of the procedure can be improved, the procedure is surprisingly accurate for cases that are of practical importance to the Navy today, in particular to the Polaris Missile subsystem and the Fleet Ballistic Missile Weapon System.

The procedure appears to have greater accuracy when the number of components is large. The presence of large differences in the sample sizes for the components has little if any effect on the accuracy, and accuracy appears to be very good when sample sizes are realistically moderate and the component reliabilities are near those of interest. The procedure can be as easily applied to an entire weapon system as it can to a subsystem, and has versatility in that several different types of test data may be used. In particular, it can be used in the development phase with the use of K-factors (degrading factors that account for differences in test and flight environments) to obtain early estimates of system reliability. Later in the program qualification test data can also be used either separately or in conjunction with data obtained earlier.

If this procedure were supplemented with Navy OD 28584, the resulting document would be one that could be used to obtain system or subsystem reliability for any weapon system without making any assumption as to the failure distribution of any type of component or subsystem.

2. Description of Procedure

For a device (system, subsystem, major component, etc.) that has k components connected in logical series, its reliability R_s , using the product rule, can be defined by

$$(2.1) \quad R_s = \prod_{i=1}^k p_i$$

where p_i is the reliability of component i . It will be understood throughout this report that when we use the term reliability we have in mind a specific mission under some fixed set of environmental conditions. In this sense, we use the term reliability in a generic manner. When applying the procedure, it makes no difference whether the components are continuously operating-type items or cycle-type items. Formula (2.1) is valid in either case. This is also true if the device, hereafter called a system, has some components of each type.

The problem of interest is to obtain a lower 100 (1 - $\frac{1}{100}$) confidence bound for the system reliability R_s using estimates of the

component reliabilities. In order to do this, we shall need the following notation:

n_i : The number of items of component i that have been put on test and given the opportunity to perform their mission.

(2.2) f_i : The number of failures for the i th component.

q_i : $1 - p_i$

\hat{q}_i : $\frac{f_i}{n_i}$

The procedure for estimating the lower confidence bound is as follows:

$$(2.3) \quad \hat{T}_i = a_i \hat{q}_i + \frac{b_i}{2} \hat{q}_i^2$$

where

$$(2.4) \quad a_i = \frac{2 n_i - 3}{2 (n_i - 1)}, \quad b_i = \frac{n_i}{n_i - 1}$$

Let

$$(2.5) \quad \hat{S} = \sum_{i=1}^k \hat{T}_i$$

and

$$(2.6) \quad \hat{r} = \left(\sum_{i=1}^k \hat{T}_i \right)^2 / \left(\sum_{i=1}^k \frac{\hat{T}_i}{n_i} \right)$$

Let $\chi^2_{\alpha, n}$ be defined by

$$(2.7) \quad P \left[\chi_n^2 > \chi^2_{\alpha, n} \right] = \alpha .$$

Then the lower 100 (1- α)% confidence bound $\hat{R}_s(\alpha)$ for R_s using this procedure is given by

$$(2.8) \quad \hat{R}_s(\alpha) = \exp \left\{ - \frac{\hat{S} [2 \hat{r}]}{\chi^2_{1-\alpha, [2 \hat{r}]}} \right\}$$

where $[2\hat{r}]$ denotes the smallest integer greater than or equal to $2r$. That is, we are asserting that

$$(2.9) \quad P[R_S \geq \hat{R}_S(\alpha)] = 1 - \alpha$$

One way to check the accuracy of this procedure is to assign values to the parameters k , n_i , q_i , find the α -th percentile point in the distribution of $\hat{R}_S(\alpha)$, and compare this point with R_S . If the procedure is exact they should be the same. This was done and the results appear in Tables 1A, 1B, and 1C.

When the sample sizes are all the same, i.e., $n_i = n$, $i = 1, 2, \dots, k$, the q_i are small and k is not large, a well-known procedure can be used to compute system reliability. This procedure is usually called the Poisson approximation method, and we have evaluated the accuracy of this procedure in the same way as described in the preceding paragraph. In Tables 1A, 1B, and 1C, Y_α is the α -th percentile point of the Poisson approximation method, and $R_{S,\alpha}$ is the α -th percentile of the new procedure suggested here. The confidence intervals obtained by either of these procedures would be exact if the respective Y_α or $R_{S,\alpha}$ equal the corresponding value of R_S in the tables. Thus $R_S - R_{S,\alpha}$ measures the accuracy of the new confidence interval procedure and $R_S - Y_\alpha$ measures the accuracy of the Poisson approximation procedure.

3. Analysis

The analysis needed to support Section 2 of this report will be supplied in the next report for this project. Some additional work needs to be done on this study to

- a) supply continuity correction factors to improve the accuracy of the procedure,
- b) construct bounds on possible errors to determine bounds on accuracy,

and

- c) establish criteria for using this procedure.

TABLE 1A
Simulation Results: $R_{s,\alpha}$ and Y_α for Given k , n_i , p_i ; All n_i Equal

No. of Components in the System	n_i	p_i	R_s	$R_{s,.05}$	$R_{s,.10}$	$R_{s,.20}$	$Y_{.05}$	$Y_{.10}$	$Y_{.20}$
5	10, $i=1, \dots, 5$.85, $i=1, \dots, 5$.44	.42	.45	.48	.08	.20	.20
5	50, $i=1, \dots, 5$.99, $i=1, \dots, 5$.951	*1.00	.895	.914	.94	.92	.92
5	100, $i=1, \dots, 5$.95, $i=1, \dots, 5$.77	.77	.77	.77	(Not available)		
15	20, $i=1, \dots, 15$.99, $i=1, \dots, 15$.86	.68	.70	.79	.76	.80	.80
15	50, $i=1, \dots, 15$.99, $i=1, \dots, 15$.86	.80	.83	.86	.85	.84	.84
30	20, $i=1, \dots, 30$.99, $i=1, \dots, 30$.74	*.60	.66	.71	.68	.67	.67
5	20, $i=1, \dots, 5$.85, $i=1, \dots, 5$.44	.44	.45	.45	.21	.23	.23
15	100, $i=1, \dots, 15$.95, $i=1, \dots, 14$							
		.85, $i=15$.79	.78	.79	.79	.77	.78	.78
15	50, $i=1, \dots, 15$.95, $i=1, \dots, 14$							
		.85, $i=15$.79	.77	.78	.79	.76	.76	.76
15	20, $i=1, \dots, 15$.95, $i=1, \dots, 14$							
		.85, $i=15$.79	.69	.71	.77	.76	.73	.72

* This error can be corrected somewhat with continuity correction factors.

TABLE 1B
Simulation Results for a System with 15 components

Component Number	n_i	P_i				
1	250	.99	}			
2	40	.99				
3	120	.99				
4	15	.99				
5	130	.99				
6	65	.99				
7	70	.99				
8	130	.99				
9	30	.99				
10	20	.99				
11	75	.99				
12	90	.99				
13	100	.99				
14	60	.99				
15	60	.99				
			R_s	$R_{s,.05}$	$R_{s,.10}$	$R_{s,.20}$
			.86	.87	.87	.87

TABLE 1C
Simulation Results for A System with 13 Components

Component Number	n_i	p_i				
1	150	.995	}	R_s	$R_{s,.05}$	$R_{s,.10}$
2	90	.985				
3	75	.979				
4	100	.988				
5	125	.982				
6	18	.980				
7	28	.967				
8	19	.900				
9	5	.980				
10	125	.995				
11	63	.970				
12	125	.995				
13	59	.968				
					$R_{s,.20}$	
				.72	.71	.69
						.71

DOCUMENT CONTROL DATA - R&D

(Security classification of title, body of abstract and indexing annotation must be entered when the overall report is classified)

1. ORIGINATING ACTIVITY (Corporate author) U. S. Naval Postgraduate School Monterey, California		2a. REPORT SECURITY CLASSIFICATION unclassified	
		2b. GROUP	
3. REPORT TITLE A Method for Computing Series System Reliability With Unequal Component Sample Sizes			
4. DESCRIPTIVE NOTES (Type of report and inclusive dates) Task Progress, June 1965 - December 1965			
5. AUTHOR(S) (Last name, first name, initial) Borsting, J. R. Woods, W. T.			
6. REPORT DATE 15 January 1966		7a. TOTAL NO. OF PAGES 8	7b. NO. OF REFS
8a. CONTRACT OR GRANT NO. b. PROJECT NO. 46058 c. Task Assignment 88432 d. Sub Project I		9a. ORIGINATOR'S REPORT NUMBER(S) TR-62 9b. OTHER REPORT NO(S) (Any other numbers that may be assigned this report)	
10. AVAILABILITY/LIMITATION NOTICES "Qualified requesters may obtain copies of this report from DDC"			
11. SUPPLEMENTARY NOTES		12. SPONSORING MILITARY ACTIVITY Special Projects Office SP-114	
13. ABSTRACT A method is presented for constructing system reliability using component failure data when the sample sizes for testing on the component parts differ greatly. The procedure can be applied to weapons systems as easily as sub-systems. No assumptions about failure distributions are made. The accuracy of the procedure was examined by computer simulations and in this manner the procedure has demonstrated high accuracy for cases of practical interest.			

14. KEY WORDS	LINK A		LINK B		LINK C	
	ROLE	WT	ROLE	WT	ROLE	WT
Reliability						
System Reliability						
Confidence Bounds						
Reliability Estimation						

INSTRUCTIONS

1. **ORIGINATING ACTIVITY:** Enter the name and address of the contractor, subcontractor, grantee, Department of Defense activity or other organization (*corporate author*) issuing the report.

2a. **REPORT SECURITY CLASSIFICATION:** Enter the overall security classification of the report. Indicate whether "Restricted Data" is included. Marking is to be in accordance with appropriate security regulations.

2b. **GROUP:** Automatic downgrading is specified in DoD Directive 5200.10 and Armed Forces Industrial Manual. Enter the group number. Also, when applicable, show that optional markings have been used for Group 3 and Group 4 as authorized.

3. **REPORT TITLE:** Enter the complete report title in all capital letters. Titles in all cases should be unclassified. If a meaningful title cannot be selected without classification, show title classification in all capitals in parenthesis immediately following the title.

4. **DESCRIPTIVE NOTES:** If appropriate, enter the type of report, e.g., interim, progress, summary, annual, or final. Give the inclusive dates when a specific reporting period is covered.

5. **AUTHOR(S):** Enter the name(s) of author(s) as shown on or in the report. Enter last name, first name, middle initial. If military, show rank and branch of service. The name of the principal author is an absolute minimum requirement.

6. **REPORT DATE:** Enter the date of the report as day, month, year; or month, year. If more than one date appears on the report, use date of publication.

7a. **TOTAL NUMBER OF PAGES:** The total page count should follow normal pagination procedures, i.e., enter the number of pages containing information.

7b. **NUMBER OF REFERENCES:** Enter the total number of references cited in the report.

8a. **CONTRACT OR GRANT NUMBER:** If appropriate, enter the applicable number of the contract or grant under which the report was written.

8b, 8c, & 8d. **PROJECT NUMBER:** Enter the appropriate military department identification, such as project number, subproject number, system numbers, task number, etc.

9a. **ORIGINATOR'S REPORT NUMBER(S):** Enter the official report number by which the document will be identified and controlled by the originating activity. This number must be unique to this report.

9b. **OTHER REPORT NUMBER(S):** If the report has been assigned any other report numbers (*either by the originator or by the sponsor*), also enter this number(s).

10. **AVAILABILITY/LIMITATION NOTICES:** Enter any limitations on further dissemination of the report, other than those

imposed by security classification, using standard statements such as:

- (1) "Qualified requesters may obtain copies of this report from DDC."
- (2) "Foreign announcement and dissemination of this report by DDC is not authorized."
- (3) "U. S. Government agencies may obtain copies of this report directly from DDC. Other qualified DDC users shall request through _____."
- (4) "U. S. military agencies may obtain copies of this report directly from DDC. Other qualified users shall request through _____."
- (5) "All distribution of this report is controlled. Qualified DDC users shall request through _____."

If the report has been furnished to the Office of Technical Services, Department of Commerce, for sale to the public, indicate this fact and enter the price, if known.

11. **SUPPLEMENTARY NOTES:** Use for additional explanatory notes.

12. **SPONSORING MILITARY ACTIVITY:** Enter the name of the departmental project office or laboratory sponsoring (*paying for*) the research and development. Include address.

13. **ABSTRACT:** Enter an abstract giving a brief and factual summary of the document indicative of the report, even though it may also appear elsewhere in the body of the technical report. If additional space is required, a continuation sheet shall be attached.

It is highly desirable that the abstract of classified reports be unclassified. Each paragraph of the abstract shall end with an indication of the military security classification of the information in the paragraph, represented as (TS), (S), (C), or (U).

There is no limitation on the length of the abstract. However, the suggested length is from 150 to 225 words.

14. **KEY WORDS:** Key words are technically meaningful terms or short phrases that characterize a report and may be used as index entries for cataloging the report. Key words must be selected so that no security classification is required. Identifiers, such as equipment model designation, trade name, military project code name, geographic location, may be used as key words but will be followed by an indication of technical context. The assignment of links, roles, and weights is optional.

DISTRIBUTION LIST

Documents Department
General Library
University of California
Berkeley, California 94720

Lockheed-California Company
Central Library
Dept. 77-14, Bldg. 170, Plt. B-1
Burbank, California 91503

Naval Ordnance Test Station
China Lake, California
Attn: Technical Library

Serials Dept., Library
University of California, San Diego
La Jolla, California 92038

Aircraft Division
Douglas Aircraft Company, Inc.
3855 Lakewood Boulevard
Long Beach, California 90801
Attn: Technical Library

Librarian
Government Publications Room
University of California
Los Angeles, California 90024

Librarian
Numerical Analysis Research
University of California
405 Hilgard Avenue
Los Angeles, California 90024

Chief Scientist
Office of Naval Research
Branch Office
1030 East Green Street
Pasadena, California 91101

Commanding Officer and Director
U. S. Navy Electronics Lab. (Library)
San Diego, California 92152

General Dynamics/Convair
P.O. Box 1950
San Diego, California 92112
Attn: Engineering Library
Mail Zone 6-157

Ryan Aeronautical Company
Attn: Technical Information
Services
Lindbergh Field
San Diego, California 92112

General Electric Company
Technical Information Center
P.O. Drawer QQ
Santa Barbara, California 93102

Library
Boulder Laboratories
National Bureau of Standards
Boulder, Colorado 80302

Government Documents Division
University of Colorado Libraries
Boulder, Colorado 80304

The Library
United Aircraft Corporation
400 Main Street
East Hartford, Connecticut 06108

Documents Division
Yale University Library
New Haven, Connecticut 06520

Librarian
Bureau of Naval Weapons
Washington, D. C. 20360

George Washington University Library
2023 G Street, N. W.
Washington, D. C. 20006

National Bureau of Standards Library
Room 301, Northwest Building
Washington, D. C. 20234

Director
Naval Research Laboratory
Washington, D. C. 20390
Attn: Code 2027

University of Chicago Library
Serial Records Department
Chicago, Illinois 60637

Documents Department
Northwestern University Library
Evanston, Illinois 60201

The Technological Institute, Library
Northwestern University
Evanston, Illinois 60201

Librarian
Purdue University
Lafayette, Indiana 47907

Johns Hopkins University Library
Baltimore
Maryland 21218

Martin Company
Science-Technology Library
Mail 398
Baltimore, Maryland 21203

Scientific and Technical Information
Facility
Attn: NASA Representative
P.O. Box 5700
Bethesda, Maryland 20014

Documents Office
University of Maryland Library
College Park, Maryland 20742

The Johns Hopkins University
Applied Physics Laboratory
Silver Spring, Maryland
Attn: Document Librarian

Librarian
Technical Library, Code 245L
Building 39/3
Boston Naval Shipyard
Boston, Massachusetts 02129

Massachusetts Institute of Technology
Serials and Documents
Hayden Library
Cambridge, Massachusetts 02139

Technical Report Collection
303A, Pierce Hall
Harvard University
Cambridge, Massachusetts 02138
Attn: Mr. John A. Harrison, Librarian

Alumni Memorial Library
Lowell Technological Institute
Lowell, Massachusetts

Librarian
University of Michigan
Ann Arbor, Michigan 48104

Gifts and Exchange Division
Walter Library
University of Minnesota
Minneapolis, Minnesota 55455

Reference Department
John M. Olin Library
Washington University
6600 Millbrook Boulevard
St. Louis, Missouri 63130

Librarian
Forrestal Research Center
Princeton University
Princeton, New Jersey 08540

U. S. Naval Air Turbine Test Station
Attn: Foundational Research Coordinator
Trenton, New Jersey 08607

Engineering Library
Plant 25
Grumman Aircraft Engineering Corp.
Bethpage, L. I., New York 11714

Librarian
Fordham University
Bronx, New York 10458

U. S. Naval Applied Science Laboratory
Technical Library
Building 291, Code 9832
Naval Base
Brooklyn, New York 11251

Librarian
Cornell Aeronautical Laboratory
4455 Genesee Street
Buffalo, New York 14225

Central Serial Record Dept.
Cornell University Library
Ithaca, New York 14850

Columbia University Libraries
Documents Acquisitions
535 W. 114 Street
New York, New York 10027

Engineering Societies Library
345 East 47th Street
New York, New York 10017

Library-Serials Department
Rensselaer Polytechnic Institute
Troy, New York 12181

Librarian
Documents Division
Duke University
Durham, North Carolina 27706

Ohio State University Libraries
Serial Division
1858 Neil Avenue
Columbus, Ohio 43210

Commander
Philadelphia Naval Shipyard
Philadelphia, Pennsylvania 19112
Attn: Librarian, Code 249c

Steam Engineering Library
Westinghouse Electric Corporation
Lester Branch Postoffice
Philadelphia, Pennsylvania 19113

Hunt Library
Carnegie Institute of Technology
Pittsburgh, Pennsylvania 15213

Documents Division
Brown University Library
Providence, Rhode Island 02912

Central Research Library
Oak Ridge National Laboratory
Post Office Box X
Oak Ridge, Tennessee 37831

Documents Division
The Library
Texas A & M University
College Station, Texas 77843

Librarian
LTV Vought Aeronautics Division
P.O. Box 5907
Dallas, Texas 75222

Gifts and Exchange Section
Periodicals Department
University of Utah Libraries
Salt Lake City, Utah 84112

Defense Documentation Center (DDC)
Cameron Station
Alexandria, Virginia 22314
Attn: IRS (20 copies)

FOREIGN COUNTRIES

Engineering Library
Hawker Siddeley Engineering
Box 6001
Toronto International Airport
Ontario, Canada
Attn: Mrs. M. Newns, Librarian

Exchange Section
National Lending Library for
Science and Technology
Boston Spa
Yorkshire, England

The Librarian
Patent Office Library
25 Southampton Buildings
Chancery Lane
London W. C. 2., England

Librarian
National Inst. of Oceanography
Wormley, Godalming
Surrey, England

Dr. H. Tjerschiold, Director
Library
Chalmers University of Technology
Gibraltargatan 5
Gothenburg S, Sweden

Lockheed Missile & Space Center
Sunnyvale, California

Department of Industrial Engineering
San Jose State College
San Jose, California

Office of Naval Research
Statistics & Logistics Branch
Department of the Navy
Washington 25, D. C.

Special Projects Office
Code SP-114
Department of the Navy
Washington, 25, D. C. (3 copies)

TA7

.U62 Borsting

no.62 A method for computing
series system reliability
with unequal component
sample sizes.

1956 71

19561

11 MAY 71

19830

19 OCT 71

19830

24 APR 72

21012

24 APR 72

20970

9 FEB 73

20970


TA7

.U62 Borsting

no.62 A method for computing
series system reliability
with unequal component
sample sizes.

98392

genTA 7.U62 no.62
A method for computing series system rel



3 2768 001 61417 5
DUDLEY KNOX LIBRARY